OMNITRONIC PS-20 Projector Speaker

Weather-proof 6.5" speaker (IP44) with mount, public address systems 100V, 20 W RMS

Art. No.: 80710368


GTIN: 4026397279658











Features:

- Durable aluminum cabinet with grille
- With mounting bracket
- Suitable for outdoor use IP44
- For application areas such as: Installation
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397279658
Weight: 2,95 kg
Length: 0.21 m
Width: 0.21 m
Heigth: 0.34 m

Technical specifications:

IP classification:	IP44
Power connection:	Fixed supply cord with open wires
Power:	Program: 40W Rated: 20W RMS
Frequency range:	110 - 15000 Hz
Sensitivity:	92 dB (1W/1m)
Max. SPL:	108 dB
Impedance:	Public address systems 100V
Attachment system:	1x Mounting bracket
Power tapping:	5W; 10W; 20W RMS via no connector/cable only switchable

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Speaker:	1 x full range loudspeaker 6.5"
Type of speaker:	Projector speaker
Material:	Aluminum
Color:	White
Dimensions:	Depth: 25.2 cm Diameter: Ø 17 cm
Weight:	2.65 kg

Scope of delivery:

1 x device
1 x user manual
1 x lid

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.