OMNITRONIC DAL-2 Ceiling Speaker

1 x 6.5" full-range speaker, public address systems 100V, 10 W RMS

Art. No.: 80710442

GTIN: 4026397414530









Features:

- 16.5 cm full-range speaker (6.5")
- Easy mounting via spring clamps, similar to standard flush-mount lights
- Steel safety rope
- Black metal grille
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397414530
Weight: 1,30 kg
Length: 0.28 m
Width: 0.28 m
Heigth: 0.10 m

Technical specifications:

Power:	Program: 20W Rated: 10W RMS
Frequency range:	80 - 18000 Hz
Sensitivity:	93 dB
Max. SPL:	97 dB
Impedance:	Public address systems 100V
Power tapping:	2.5W; 5W; 10W RMS via screw terminal switchable
Speaker:	1 x full range loudspeaker 6.5"
Type of speaker:	On ceiling/on wall speaker
Material:	ABS Acrylonitrile butadiene styrene

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Color:	White, scratchproof and shockproof
Dimensions:	Depth: 8.8 cm Diameter: Ø 26.4 cm
Weight:	1.15 kg

Scope of delivery:

1 x device
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.