OMNITRONIC WP-4W PA Wall Speaker

2-way speaker with mount, public address systems 100V, 20 W RMS

Art. No.: 80710511

GTIN: 4026397412093









Features:

- 2-way system
- Trapezoidal cabinet for corner installation
- With mounting bracket
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397412093
Weight: 2,55 kg
Length: 0.23 m
Width: 0.21 m
Heigth: 0.28 m

Technical specifications:

Power connection:	Fixed supply cord with open wires
Power:	Program: 40W Rated: 20W RMS
Frequency range:	90 - 20000 Hz
Sensitivity:	89 dB
Max. SPL:	101 dB
Impedance:	Public address systems 100V
Attachment system:	2x M6 thread 1x mounting bracket
Connections:	Input: supply cord with open wires
Speaker:	1 x woofer 4"

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	PP polypropylene 1 x tweeter 1" PP polypropylene with wave guide
Type of speaker:	Compact cabinet speaker
Type of construction:	Closed Box
Material:	ABS Acrylonitrile butadiene styrene
Color:	White, scratchproof and shockproof
Dimensions:	Width: 17 cm Depth: 15 cm Height: 21.5 cm
Weight:	2.10 kg

Scope of delivery:

1 x device
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.