OMNITRONIC WP-5W PA Wall Speaker

2-way speaker with mount, public address systems 100V, 30 W RMS

Art. No.: 80710521

GTIN: 4026397412130









Features:

- 2-way bass-reflex system
- Trapezoidal cabinet for corner installation
- With mounting bracket
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

EAN / GTIN: 4026397412130
Weight: 3,05 kg
Length: 0.23 m
Width: 0.23 m
Heigth: 0.28 m

Technical specifications:

Power connection:	Fixed supply cord with open wires
Power:	Program: 60W Rated: 30W RMS
Frequency range:	90 - 20000 Hz
Sensitivity:	89 dB
Max. SPL:	103 dB
Impedance:	Public address systems 100V
Attachment system:	Mounting bracket
Speaker:	1 x woofer 5"
Type of speaker:	Compact cabinet speaker
Material:	ABS Acrylonitrile butadiene styrene
Color:	White, scratchproof and shockproof

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Dimensions:	Width: 18.2 cm Depth: 16.2 cm Height: 24.2 cm
Weight:	2.55 kg

Scope of delivery:

1 x device
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.