OMNITRONIC HS-52 Horn Speaker

Weather-proof 5" speaker (IP66) with mount, public address systems 100V, 30 W RMS

Art. No.: 80710823

GTIN: 4026397726671











Features:

- High sound pressure and wide frequency range
- 13 cm cone speaker (5") for well-balanced sound
- For outdoor amplifying systems in football stadiums, outdoor pools, open air events
- Grey aluminum grille
- Suitable for outdoor use IP66
- For application areas such as: Installation

Logistic

EAN / GTIN: 4026397726671
Weight: 4,14 kg
Length: 0.40 m
Width: 0.24 m
Heigth: 0.38 m

Technical specifications:

IP classification:	IP66
Cable length:	0.3 m
Power:	Program: 60W Rated: 30W RMS
Frequency range:	125 - 8500 Hz
Sensitivity:	93 dB (1W/1m)
Max. SPL:	108 dB public address systems 100V; 111 dB 8 ohms
Impedance:	Public address systems 100V; 8 ohms
Power tapping:	3.8W; 7.5W; 15W; 30W RMS via selector switch switchable
Connections:	Supply cord with open wires

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Speaker:	Full range loudspeaker 5" with ferrit magnet Basket material: steel Conematerial: weatherproof Cardboard/paper
Type of speaker:	On ceiling/on wall speaker; horn
Material:	ABS Acrylonitrile butadiene styrene; aluminum
Color:	Grey
Dimensions:	Width: 36.6 cm Depth: 28 cm Height: 17.2 cm
Weight:	3.12 kg

Scope of delivery:

1 x speaker
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.