OMNITRONIC ED-60T Horn Driver

Weather-proof driver, 70/100 V or 16 ohms, 60 W RMS

Art. No.: 80710890

GTIN: 4026397303025





List price: 65.33 €

incl. 19% VAT.

Features:

- Power selector switch
- 35 mm mounting flange (3.5 cm/1 3/8")
- Suitable for outdoor use IP44

Logistic

EAN / GTIN: 4026397303025
Weight: 2,43 kg
Length: 0.13 m
Width: 0.12 m
Heigth: 0.19 m

Technical specifications:

IP classification:	IP44
Cable length:	1 m
Power:	Program: 120W Rated: 60W RMS
Frequency range:	350 - 5000 Hz
Sensitivity:	108 dB
Impedance:	Public address systems 100V; Public address systems 70V; 16 ohms
Power tapping:	7.5W; 15W; 30W; 60W RMS via no connector/cable only switchable
Speaker:	Horn vent 1.35"
Type of speaker:	Horn
Color:	Grey
Dimensions:	Height: 17.3 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Diameter: Ø 12.2 cm
Weight:	2.34 kg

Scope of delivery:

1 x speaker
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.