



## GE 4515 PAR-36 6,4V/30W VNSP 100h

PAR-36 lamp

Art. No.: 88061000

GTIN: 5994100022114



### Features:

- Clearly separated beam
- Harmless for color-foils
- The heat permeates the front-glass continuously
- For professional effect-illumination in discotheques
- Color temperature approx. 3000 K
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 5994100022114

Weight: 0,22 kg

Length: 0.10 m

Width: 0.10 m

Height: 0.10 m

### Technical specifications:

|                     |                                                                          |
|---------------------|--------------------------------------------------------------------------|
| Voltage (lamps):    | 6.4 V, AC                                                                |
| Nominal wattage:    | 30 W                                                                     |
| Base:               | G-53 STC                                                                 |
| Lamp type:          | Halogen lamp; clear lamp; low voltage lamp; reflector lamp; halogen bulb |
| Lamp specification: | Dimmable<br>Hot restrike                                                 |
| Beam angle:         | 15°                                                                      |
| Color of light:     | White                                                                    |

|                              |                  |
|------------------------------|------------------|
| Color temperature:           | 3000K            |
| Color rendering index (CRI): | 95 Ra            |
| Lead time:                   | 0 s              |
| Construction:                | PAR-36           |
| Operating temperature max.:  | 40° C            |
| Operating temperature min.:  | 10° C            |
| Burning position:            | S180 (universal) |
| Lamp life:                   | 100 h            |
| Lamp current:                | 4.69 A           |
| Dimensions (LxD):            | 70x114 mm        |
| Weight:                      | 0.18 kg          |

**Scope of delivery:**

---