OMNILUX®

OMNILUX PAR-36 6.4V/30W G-53 VNSP 200h

PAR-36 lamp

Art. No.: 88061005

GTIN: 4026397102277

List price: 6.55 €

incl. 19% VAT.

Description:

The PAR-36 lamp from Omnilux : For professional effect lighting in discotheques

The double-ended PAR-36 shines in a pleasant warm white with a sharply defined beam of light. It is gentle on color foil, dimmable and emits even heat through the front glass.
The beam angle of the light source is 6°.

The rated output is 30W.

Logistic

EAN / GTIN: 4026397102277
Weight: 0,25 kg
Length: 0.09 m
Width: 0.09 m
Heigth: 0.10 m

Features:

- Harmless for color-foils
- The heat permeates the front-glass continuously
- Dimmable
- Very high color rendering index (CRI)

Technical specifications:

Operating voltage:	6.4 V
Nominal wattage:	30 W
Base:	G-53 STC
Lamp type:	Incandescent lamp; halogen lamp
Lamp specification:	Dimmable

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Beam angle:	6°
Color of light:	Warm white WW <3300 K
Color rendering index (CRI):	99 Ra
Lead time:	0.2 s
Construction:	PAR-36
Operating temperature max.:	+40° C
Operating temperature min.:	-20° C
Burning position:	S180 (universal)
Lamp life:	200 h
Luminous flux:	510 lm
Wavelength:	778 nm
Dimensions (LxD):	70x114 mm
Weight:	0.21 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1015336

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.