OSRAM 64642HLX FDV 24V/150W G-6,35 300h

Art. No.: 88288011

GTIN: 4050300012025



Features:

- Dimmable
- Very high color rendering index (CRI)
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4050300012025
Weight: 0,01 kg
Length: 0.07 m
Width: 0.03 m
Heigth: 0.03 m

Technical specifications:

Operating voltage:	24 V
Nominal wattage:	150 W
Base:	G-6.35
Lamp type:	Incandescent lamp; halogen lamp
Lamp specification:	Dimmable
Beam angle:	310°
Color of light:	White
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	10° C

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Burning position:	S90 (BDTH, base down to ±90°)
Lamp life:	300 h
Luminous flux:	5000 lm
Weight:	0.01 kg
Energy efficiency class (A - G):	G

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.