



List price: 70.21 €
incl. 19% VAT.

Description:

Basics:
GS=Gap Short (shortened electrode space)
DE=Double Ended (double-sided lamp with threaded pin)
SE=Single Ended (one-sided lamp)
PAR=Lamp built in a parabolic reflector
HMP=Due to their special filling and to their electrode system, HMP-lamps cannot only be "dimmed", but also be "boosted", i. e. be operated beyond their rated power. During this, the light technical characteristics, such as color temperature, color rendering index and light output are practically constant during "dimming" and "boosting".

Logistic

EAN / GTIN: 4026397139846
Weight: 0,08 kg
Length: 0.15 m
Width: 0.06 m
Heigth: 0.04 m

Features:

- Good color rendering index (CRI)

Technical specifications:

Operating voltage:	95 V
Nominal wattage:	575 W
Base:	GX9.5
Lamp type:	Discharge lamp
Color temperature:	7200K
Color rendering index (CRI):	85 Ra

Burning position:	S180 (universal)
Lamp life:	500 h
Luminous flux:	49000 lm
Lamp current:	7 A
Dimensions (LxD):	125x28 mm
Weight:	0.05 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1612602

Scope of delivery: